

# COMPETITION PLUS VALVES - BLANKS

**Ferrea** also offers competition **Plus Blanks Valves** that can be custom-machine to your specifications. Racing Valves not in stock can be custom made for within days. Check with us for pricing and lead time.



COMPETITION PLUS VALVES - BLANKS

Part N°	Type	Head Diam.	Stem Diam.	Overall Length	Tip Length	References
<b>BLANKS (5/16) ("REQUIRE LASH CAPS or HARD TIPS")</b>						
F1185P	E	1.575	5/16	5.315	BLANK	15° Flo. Finished.No groove. Special Alloy
F806607	E	1.580	.3085	5.870	BLANK	15° Flo.
F1475P	E	1.650	5/16	6.300	BLANK	12° Flo. Dish Head. (Super Alloy)
F1487P	E	1.650	5/16	6.300	BLANK	24° Flo. Tulip. Super Alloy
F1177P	E	1.650	5/16	7.500	BLANK	12° Flo. Hi Temp Special Alloy
F1197P	E	1.800	5/16	7.000	BLANK	24° Flo. Tulip. HiTe.Finished. No groove. Spec. Alloy
F1233P	E	1.950	5/16	6.500	BLANK	15° Flo. Finished.No groove. Special Alloy
F1237P	E	2.000	5/16	7.000	BLANK	22° Flo. Tulip Flo - Finished No groove. Spec. Alloy
F806608	I	1.930	.3085	5.870	BLANK	12° Flo.
F1248P	I	2.080	5/16	7.000	BLANK	12° Super Flo. Finished. No groove. Spec. Alloy
F1245P	I	2.125	5/16	7.000	BLANK	12° Super Flo. Finished. No groove. Spec. Alloy
F1246P	I	2.150	5/16	7.000	BLANK	12° Super Flo. Finished. No groove. Spec. Alloy
F1247P	I	2.250	5/16	7.000	BLANK	12° Super Flo. Finished. No groove. Spec. Alloy
F1510P	I	2.300	5/16	7.000	BLANK	24° Tulip Flo.Finished.No groove. Special Alloy
F1243P	I	2.350	5/16	7.000	BLANK	12° Super Flo. Finished.No groove. Spec. Alloy
<b>BLANKS (1 1/32) ("REQUIRE LASH CAPS or HARD TIPS")</b>						
F1888P	E	1.625	11/32	7.000	BLANK	24° Flo. Special Alloy
F1590P	E	1.650	11/32	7.000	BLANK	23.5° Flo. Super Alloy. <b>Turbo Applications</b>
F1184P	E	1.650	11/32	7.500	BLANK	15° Super Flo. HiTe Alloy. Finished.No groove
F1889P	E	1.650	11/32	7.000	BLANK	24° Flo. Special Alloy
F1196P	E	1.800	11/32	7.000	BLANK	24° Super Flo. Tulip.HiTe Special Alloy
F1589P	E	1.800	11/32	7.000	BLANK	23.5° Flo. Super Alloy. <b>Turbo Applications</b>
F1591P	E	1.800	11/32	7.000	BLANK	15° Super Flo. Special Alloy
F1181P	E	2.000	11/32	7.000	BLANK	15° Super Flo. Flat Head. Finished.No groove
F1183P	E	2.000	11/32	7.000	BLANK	15° Super Flo. Finished.No groove
F1509P	E	2.000	11/32	7.000	BLANK	22° Tulip Flo. Pro-T/F-F/C. (Super Alloy)
F1890P	I	2.150	11/32	7.000	BLANK	12° Flo. Special Alloy
F1891P	I	2.200	11/32	7.000	BLANK	12° Flo. Special Alloy
F1190P	I	2.375	11/32	7.000	BLANK	12° Super Flo. Finished.No groove. Special Alloy
F1191P	I	2.375	11/32	7.000	BLANK	12° S. Flo. Flat Head.Finished.No groove. Spec. Alloy
F1193P	I	2.600	11/32	7.000	BLANK	12° Super Flo. Finished. No groove. Special Alloy
<b>BLANKS (3/8) ("REQUIRE LASH CAPS or HARD TIPS")</b>						
F1572P	E	1.925	3/8	5.219	BLANK	22° Flo. 55° Seat / 38° Backcut. - Sup Alloy. T/F-F/C
F1594P	E	1.940	3/8	7.000	BLANK	15° Super Flo. Special Alloy
F1530P	E	1.950	3/8	5.170	BLANK	22° Flo-DART/55° Seat-Turbo/T Fuel/Funny Car-Hi Temp (Super Alloy)
F1511P	E	2.100	3/8	7.000	BLANK	22° Flo. (Super Alloy).Funny Car/Top Fuel
F1592P	I	2.350	3/8	7.000	BLANK	12° Super Flo.
F1593P	I	2.375	3/8	7.000	BLANK	12° Super Flo. Special Alloy. Flat Head
<b>BLANKS 4-5 MM ("REQUIRE LASH CAPS OR HARD TIPS")</b>						
F0066	E	23 mm	4 mm	125 mm	BLANK	21° Flo-No Groove-No Tip. Special Alloy
F0064	E/I	26.5 mm	4 mm	125 mm	BLANK	21° Flo-No Groove-No Tip. Special Alloy
F0232	I	30 mm	4 mm	135 mm	BLANK	21° Super Flo. Special Alloy
F0173	E	28.5 mm	4.46 mm	120 mm	BLANK	12° Flo-No Groove-No Tip. Special Alloy
F0171	I	31 mm	4.48 mm	120 mm	BLANK	12° Flo Bimetallic. Special Alloy
F0172	I	31 mm	4.48 mm	120 mm	BLANK	15° Flo Bimetallic. Special Alloy
F0063	E	26 mm	4.5 mm	125 mm	BLANK	21° Flo-No Groove-No Tip. Special Alloy
F0062	I	34 mm	4.5 mm	125 mm	BLANK	19° Flo-No Groove-No Tip. Special Alloy
F0183	E	29 mm	4.95 mm	130 mm	BLANK	12° Flo. Special Alloy
F0337	E	27 mm	4.97 mm	135 mm	BLANK	19° Flo. Special Alloy. Bi-Metallic
F0069	E	34 mm	4.97 mm	140 mm	BLANK	19° Flo. Super Alloy.
F0184	I	34 mm	4.97 mm	130 mm	BLANK	12° Flo. Special Alloy
F0338	I	32.1 mm	4.98 mm	135 mm	BLANK	19° SuperFlo. Dish Head

# COMPETITION PLUS VALVES - BLANKS

Part N°	Type	Head Diam.	Stem Diam.	Overall Length	Tip Length	References
<b>BLANKS 5-6 MM ("REQUIRE LASH CAPS OR HARD TIPS")</b>						
F0067	I	30 mm	5 mm	135 mm	BLANK	19° Flo-No Groove-No Tip. Special Alloy
F0065	E/I	38 mm	5 mm	135 mm	BLANK	19° Super Flo-No Groove-No Tip. Special Alloy
F0242	E	34 mm	5.48 mm	135 mm	BLANK	15° Flo. Flat Head. Special Alloy
F1943P	E	32 mm	5.48 mm	140 mm	BLANK	22° Flo. Super Alloy <b>Turbo Applications</b>
F1459P	E	32 mm	5.48 mm	135 mm	BLANK	22° Flo. Super Alloy
F1457P	I	37 mm	5.48 mm	135 mm	BLANK	20° Flo. Special Alloy
F0241	I	41 mm	5.48 mm	135 mm	BLANK	14° Super Flo. Flat Head. Special Alloy
F0231	E	30 mm	5.5 mm	135 mm	BLANK	19° Flo. Dish Head. Top Fuel. Super Alloy
F0238	E	32 mm	5.5 mm	135 mm	BLANK	22° Flo-No Groove-No Tip. Special Alloy
F0047	I	34 mm	5.5 mm	135 mm	BLANK	19° Super Flo-No Groove-No Tip. Special Alloy
F0233	I	36 mm	5.5 mm	135 mm	BLANK	25° Super Flo. HONDA. Special Alloy
F0253	I	42 mm	5.5 mm	135 mm	BLANK	19° Super Flo. Special Alloy
F1492P	E	34 mm	5.95 mm	140 mm	BLANK	21° Tulip Flo. Bimetallic Super Alloy
F1942P	E	34 mm	5.95 mm	140 mm	BLANK	21° Flo. Super Alloy <b>Turbo Applications</b>
F0176	E	36 mm	5.95 mm	135 mm	BLANK	21° Flo. Special Alloy
F0175	E	36 mm	5.96 mm	135 mm	BLANK	21° Super Flo-No Groove-No Tip. Special Alloy
F1580P	I	36 mm	5.97 mm	145 mm	BLANK	12° Super Flo-No Groove-No Tip. Special Alloy
F1581P	I	38 mm	5.97 mm	145 mm	BLANK	15° Super Flo-No Groove-No Tip. Special Alloy
F0174	I	42 mm	5.97 mm	135 mm	BLANK	19° Super Flo-No Groove-No Tip. Special Alloy
F0293	I	46 mm	5.97 mm	145 mm	BLANK	19° Super Flo. Special Alloy.
F1582P	I	46 mm	5.97 mm	145 mm	BLANK	12° Super Flo-No Groove-No Tip.
<b>BLANKS 6-7 MM ("REQUIRE LASH CAPS OR HARD TIPS")</b>						
F0060	I	40 mm	6 mm	145 mm	BLANK	19° Super Flo-No Groove-No Tip. Special Alloy
F1595P	E	31 mm	6.02 mm	145 mm	BLANK	25° Flo. Special Alloy. Ford
F1596P	I	36 mm	6.03 mm	145 mm	BLANK	19° Super Flo. Ford
F1455P	E	32.5 mm	6.55 mm	135 mm	BLANK	22° Flo Super Alloy
F1941P	E	32.5 mm	6.55 mm	140 mm	BLANK	22° Flo Super Alloy <b>Turbo Applications</b>
F1453P	E	36 mm	6.57 mm	135 mm	BLANK	20° Super Flo. Special Alloy
F1438P	I	38 mm	6.58 mm	135 mm	BLANK	20° Super Flo
F1585P	E	34 mm	6.95 mm	145 mm	BLANK	15° Flo. No groove-No Tip. Special Alloy
F1586P	I	39 mm	6.97 mm	145 mm	BLANK	12° Super Flo. No Groove-No Tip. Special Alloy
F1419P	E	34.5 mm	6.98 mm	135 mm	BLANK	30° Flo. Special Alloy
F1418P	I	40 mm	6.98 mm	135 mm	BLANK	20° Super Flo. Special Alloy
F0077	E	1.750	.275	5.710	BLANK	24° Tulip Flo. Special Alloy Harley Davidson
F0078	I	2.100	.275	5.710	BLANK	24° Tulip Flo. Harley Davidson
<b>BLANKS (7 mm) ("REQUIRE LASH CAPS or HARD TIPS")</b>						
F1473P	E	1.600	7mm	6.300	BLANK	24° Tulip. NASCAR (Super Alloy)
F1472P	E	1.625	7mm	6.300	BLANK	12° NASCAR (Super Alloy)
F1486P	E	1.625	7mm	6.300	BLANK	24° Tulip. NASCAR (Super Alloy)
F1493P	E	1.650	7mm	6.300	BLANK	24° Tulip. (Super Alloy)
F2207P	I	2.080	7mm	6.500	BLANK	12° Flo. Ultra Light. Special Alloy
F2208P	I	2.150	7mm	6.500	BLANK	12° Flo. Ultra Light. Special Alloy
F2209P	I	2.250	7mm	6.500	BLANK	12° Flo. Ultra Light. Special Alloy
<b>BLANKS (7-8 mm) ("REQUIRE LASH CAPS or HARD TIPS")</b>						
F0004	E	33 mm	7mm	135 mm	BLANK	22° Flo-No Groove-No Tip. Special Alloy
F0345	E	33mm	7mm	145mm	BLANK	22° Flo. Super Alloy. No Groove. No Tip
F0034	E	36 mm	7mm	135 mm	BLANK	22° Flo-No Groove-No Tip. Special Alloy
F0346	E	39mm	7mm	145mm	BLANK	22° Flo. Super Alloy. No Groove. No Tip
F0038	E	39 mm	7mm	135 mm	BLANK	22° Tulip Flo-No Groove-No Tip. Special Alloy
F0002	I	42 mm	7mm	135 mm	BLANK	20° Flo-No Groove-No Tip. Special Alloy
F0039	I	46 mm	7mm	145 mm	BLANK	12° Flo-No Groove-No Tip. Special Alloy
F2162P	E	32mm	7.09mm	145mm	BLANK	R. 12mm Flo. Flat Head
F2163P	I	38mm	7.10mm	145mm	BLANK	19° Super Flo. Flat Head
F0029	E	1.750	.308	5.118	BLANK	24° Flo-No Groove-No Tip. Special Alloy.
F1583P	E	1.650	.313	6.000	BLANK	15° Super Flo. Special Alloy. GM LS7/L92
F2159P	E	1.650	.313	8.000	BLANK	15° Flo. <b>Super Alloy</b> . GM LS1/LS7/L92
F1584P	E	1.650	.313	6.000	BLANK	24° Super Flo. Special Alloy. GM LS7/L92
F1599P	E	1.650	.313	6.000	BLANK	24° Flo. <b>Super Alloy</b> . GM LS1/LS7/L92
F0230	E	41 mm	7.96mm	135 mm	BLANK	20° Super Flo. DUCATI. Special Alloy
F1587P	I	2.000	.3135	6.000	BLANK	12° Super Flo. GM LS1/LS6
F1588P	I	2.200	.3135	6.000	BLANK	12° Super Flo. GM LS7/L92
F0229	I	47 mm	7.98mm	135 mm	BLANK	20° Super Flo. DUCATI. Special Alloy
F1182P	E	41 mm	8mm	135 mm	BLANK	15° Super Flo. Finished. No groove. Special Alloy
F1442P	I	44 mm	8mm	110 mm	8.5 mm	10° Super Flo. Special Alloy
F1192P	I	48 mm	8mm	135 mm	BLANK	26° Super Flo. Finished. No Groove. Special Alloy