

# SPORT COMPACT COMPETITION PLUS VALVES

Part N°	Type	Head Diam.	Stem Diam.	Overall Length	Tip Length	References
<b>AUDI 1.8T / VW 20 VALVE - 1996-2002</b>						
<b>AUDI 2.7T - DOHC 30 VALVE (APB) 1998-2004</b>						
F1554P	E	29.9 mm	5.96 mm	103.92 mm	5 mm	26° Flo. Stk size. Trip. groove. <b>2 Valves required</b>
F1555P	E	30.9 mm	5.96 mm	103.92 mm	5 mm	26° Flo. +1mm o/s. Trip. groove. <b>2 Valves required</b>
F1556P	I	26.9 mm	5.97 mm	105.1 mm	5 mm	24° Sup. Flo. Stk size. Trip. groove. <b>3 Val. required</b>
F1557P	I	27.9 mm	5.97 mm	105.1 mm	5 mm	24° Sup. Flo. +1mm o/. Trip. groove. <b>3 Val. required</b>
<b>BMW 3 SERIES (M50-M051-M52)</b>						
F1552P	E	30.5 mm	5.96 mm	106 mm	3.7 mm	25° Flo. Stock size. Triple groove
F1553P	E	31.5 mm	5.96 mm	106 mm	3.7 mm	25° Flo. 1+mm o/size. Triple groove
F1550P	I	32.95 mm	5.97 mm	106.1 mm	3.7 mm	12° Super Flo. Stock size. Triple groove
F1551P	I	33.95 mm	5.97 mm	106.1 mm	3.7 mm	12° Super Flo. 1+mm o/size. Triple groove
<b>CHRYSLER/DODGE 3.5L - SOHC V6 24 VALVE - 1998-2004</b>						
F1574P	E	29 mm	6.92 mm	125.94 mm	5.9 mm	22° Flo. Stock size. Super Alloy. Single Groove
F1575P	E	30 mm	6.92 mm	125.94 mm	5.9 mm	22° Flo. 1 mm oversize. Super Alloy. Single Groove
F1576P	I	36.5 mm	6.94 mm	114.7 mm	3.5 mm	19° Super Flo. Stock size. Single Groove
F1577P	I	37.5 mm	6.94 mm	114.7 mm	3.5 mm	19° Super Flo. 1mm oversize. Single Groove
<b>Tech Note: These Ferrea Racing Valves come with single radial grooves. For racing applications Ferrea Racing does not recommend the use of triple radial grooved valves.</b>						
<b>DODGE NEON 2.0 - DOHC 16 VALVE - 1994-1999</b>						
F1544P	E	30.5 mm	5.9 mm	109.80 mm	11 mm	24° Tulip. Stock Size
F1545P	I	34.75 mm	5.93 mm	111.75 mm	11 mm	14° Super Flo. Stock size
<b>DODGE NEON 2.0 - SOHC 16 VALVE - 1994-1999</b>						
F1541P	E	28.75mm	5.918mm	117.20mm	5.10mm	28° Tulip. Stock size
F1543P	E	29.75mm	5.918mm	117.20mm	5.10mm	28° Tulip. 1 mm oversize
F1540P	I	33.25mm	5.944mm	114.95mm	6.65mm	17° Super Flo. Stock size
F1542P	I	34.25mm	5.944mm	114.95mm	6.65mm	17° Super Flo. 1 mm oversize
<b>DODGE NEON 2.4 - SRT4 - DOHC 16 VALVE (A853) - 2003-2005</b>						
F2141P	E	28.36 mm	5.95 mm	109.80 mm	9.1 mm	21° Flo. Stock size. Super Alloy. Turbo Application. Single Groove
F2142P	E	29.36 mm	5.95 mm	109.80 mm	9.1 mm	21° Flo. 1mm Over Size Super Alloy. Turbo Application. Single Groove
F2143P	I	34.81 mm	5.96 mm	111.7 mm	11.05 mm	21° Super Flo. Stock size. Single Groove
F2144P	I	35.81 mm	5.96 mm	111.7 mm	11.05 mm	21° Super Flo. 1mm oversize. Stock Size. Single Groove
<b>Tech Note: These Ferrea Racing Valves come with single radial grooves. For racing applications Ferrea Racing does not recommend the use of triple radial grooved valves. These valves are designed to be used only with Ferrea Valve Train Kit components.</b>						
<b>FORD ESCORT 2.0L - DOHC ZETEC 16 VALVE (ZX2) - 1999-2001</b>						
<b>FORD FOCUS 2.0L - DOHC ZETEC 16 VALVE (ZX3) - 2000-2001</b>						
F1817P	E	27.96 mm	6.012 mm	97.16 mm	5.25 mm	25° Flo. Stock size. Super Alloy
F1818P	E	28.96 mm	6.012 mm	97.16 mm	5.25 mm	25° Flo. 1 mm oversize. Super Alloy
F1959P	E	28.96 mm	5.5 mm	97.16 mm	5.25 mm	25° Flo. 1 mm oversize. Super Alloy
F1819P	I	32 mm	6.03 mm	97.55 mm	5.25 mm	25° Super Flo. Stock size
F1820P	I	33 mm	6.03 mm	97.55 mm	5.25 mm	25° Super Flo. 1 mm oversize
F1960P	I	33 mm	5.5 mm	97.55 mm	5.25 mm	25° Super Flo. 1 mm oversize
<b>FORD 2.3L - DOHC ZETEC 16 VALVE - 2002</b>						
F1910P	E	29.96 mm	5.47 mm	104.78 mm	4 mm	20° Flo. Stock size. Super Alloy
F1911P	E	30.96 mm	5.47 mm	104.78 mm	4 mm	20° Flo. 1 mm oversize. Super Alloy
F1908P	I	35.08 mm	5.48 mm	103.6 mm	4 mm	20° Super Flo. Stock size
F1909P	I	36.08 mm	5.48 mm	103.6 mm	4 mm	20° Super Flo. 1 mm oversize
<b>FORD FOCUS SVT - 2002-2003</b>						
F1923P	E	27.97 mm	6.02 mm	102.30 mm	5.20 mm	25° Flo.
F1925P	E	28.97 mm	6.02 mm	102.30 mm	5.20 mm	25° Flo. + 1 mm oversize
F1922P	I	33.53 mm	6.03 mm	102.80 mm	3.20 mm	25° Super Flo.
F1924P	I	34.53 mm	6.03 mm	102.80 mm	3.20 mm	25° Super Flo. + 1 mm oversize.
<b>GM 2.2 ECO TEC</b>						
F1961P	E	30.1 mm	5.96 mm	101.5 mm	5.5 mm	22° Flo. Stock size
F1962P	E	31.1 mm	5.96 mm	101.5 mm	5.5 mm	22° Flo. 1 mm oversize
F1963P	I	35.1 mm	5.97 mm	102.5 mm	5.5 mm	20° Super Flo. Stock size
F1964P	I	36.1 mm	5.97 mm	102.5 mm	5.5 mm	20° Super Flo. 1 mm oversize